

# LAUGFS XTRALIFT PNEUMATIC FORKLIFT TYRES



**LAUGFS XTRALIFT TYRES** are designed with heavy-duty carcass and high abrasion-resistant tread, delivering both incredible puncture resistance and longer life.



**LAUGFS**  
INDUSTRIAL TYRES



### XTRALIFT

Reinforced sidewall for side impact protection and extra performance features make the tyre unstoppable. Its unique tread design delivers a smooth, comfortable ride with exceptional overall tyre life, while providing superior endurance and durability.

- The deep tread with extra thick sidewalls and strong casing  
Provide exceptional durability and minimize the risk of punctures and accidental damages.
- Natural rubber based tread compound with right blend of reinforcing materials  
Provides greater chip and tear /chunking resistance.
- Specially designed rim guard  
Ensures protection against flat and wheel damages in the rim flange area.

LAUGFS XTRALIFT											
Tire Size	PR	Rim Width (inch)	TT / TL	Section Width		OD		Load Capacity (kg)		Inflation Pressure (psi)	Speed (kmph)
				mm	inch	mm	inch	Load Wheel	Steering wheel		
5.00-8	8	3	TT	134	5.3	472	18.6	-	830	115	25
5.00-8	10	3	TT	134	5.3	472	18.6	1415	1091	145	25
18x7-8	16	4.33	TT	168	6.6	465	18.3	2145	1640	145	25
6.00-9	10	4	TT	164	6.5	549	21.6	1515	1280	125	25
6.50-10	12	5	TT	183	7.2	596	23.5	1935	1635	140	25
7.00-12	14	5	TT	192	7.6	690	27.2	2670	2255	145	25
250-15	18	7.5	TT	250	9.8	735	28.9	4105	3470	150	25
300-15	20	8	TT	300	11.8	840	33.1	5940	4990	135	25
7.00-15	14	6	TT	203	8.0	758	29.8	3090	2610	145	25
7.50-15	14	6	TT	205	8.1	772	30.4	3505	2965	140	25
28x9-15 / 8.15 - 15	14	7	TT	225	8.9	716	28.2	3075	2595	140	25
8.25-15	14	6.5	TT	242	9.5	852	33.5	3830	3235	120	25
8.25-15	16	6.5	TT	242	9.5	852	33.5	4615	3550	131	25
10.00-20	18	7.5	TT	284	11.2	1080	42.5	-	6900	145	30
12.00-20	20	8.5	TT	320	12.6	1151	45.3	9231	7101	145	25