

SKS SUPER SOLID

- 13.00 - 24 / 14.00 - 24



LAUGFS SUPER SOLID TYRES are designed for tough on the road and off the road construction machineries and vehicles. It is designed with an extra deep directional tread and deep lugs to provide traction and durability. The wide-tread pattern and extra thick sidewall prevents tire distortion while cornering. Its self-cleaning design keeps the tyre clean of mud and dirt, and makes the machine more energy efficient.



LAUGFS
INDUSTRIAL TYRES



LOADER GRIP



SOLID GRIP

- An open spaced traction pattern with self-cleaning property provides traction capability resulting in ease driving on heavy dirt and mud conditions.
- Wide based flat tread with large contact area for even distribution of ground contact pressure.
- Tough carcass & special tread compound to withstand cuts, bruises in severe operating conditions for increased service life.
- Its two row Aperture sidewall design makes excellent cushion function and driving comfort.

SKS -Super Solid												
Tyre Size	Rim Size	Easy Fit /Normal	Tread Pattern	Tyre Dimension				Load Capacity (kg)			Finished tyre weight(kg)	Pcs/20ft
				Inch		mm		Other Vehicles (Trailers)				
				Max Width	O.D.+/- 2%	Max Width	O.D.+/- 2%	Up to 6Km/h	Up to 10Km/h	Up to 25Km/h		
13.00-24	8.50-24	N	SKS- APP 2FA	12.8	50.4	325	1280	7700	7000	6350	280	49
14.00-24	8.50-24	N	SKS- APP 2FA	13.9	52.4	352	1332	11100	10100	9300	321	36
17.5-25	14.00 - 25	N	LOADER GRIP	17.3	52.8	440	1340	9680	8800	8000	496	20
20.5-25	17.00-25	N	LOADER GRIP	20.9	58.7	530	1490	10890	9900	9000	782	16
20.5-25	17.00-25	N	SMOOTH	20.9	57.9	530	1470	10890	9900	9000	803	16
23.5-25	19.50-25	N	LOADER GRIP	22.8	63.4	580	1610	12100	11000	10000	1076	12
23.5-25	19.50-25	N	LOADER GRIP +	22.8	63.4	580	1610	12100	11000	10000	1100	12
23.5-25	19.50-25	N	LOADER SM	22.8	62.6	580	1590	12100	11000	10000	1083	12